

15-5 All

| Sheet | Spec | Thk | Width | Length |
|--|------------------------|--------------|-----------|------------|
| 15-5 Sheet 2D Finish Cond A | AMS-5862 / BMS 7-240D | 0.032 | 9 | 12.5 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862K / BMS 7-240H | 0.032 | 36 | 59 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862K / BMS 7-240H | 0.032 | 36 | 120 |
| 15-5 Sheet A. HT To 180-200KSI | AMS-5862 / BMS 7-240D | 0.04 | 1 | 4 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862 / BMS 7-240D | 0.04 | 3.75 | 23.875 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862L / BMS 7-240 | 0.04 | 36 | 22.375 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862J/BMS-7-240 | 0.05 | 12 | 23.875 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862K / BMS-7-240 | 0.05 | 36 | 50.5 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862L / BMS-7-240 | 0.05 | 36 | 120 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862L / BMS-7-240 | 0.05 | 36 | 120 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862L / BMS-7-240 | 0.05 | 36 | 79 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862J/BMS-7-240 | 0.063 | 36 | 33.25 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862J/BMS-7-240 | 0.063 | 11.875 | 17.625 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862J/BMS-7-240 | 0.063 | 11.875 | 23.5 |
| 15-5 Sheet A. 2D Finish HT To 180-200KSI BAC 5619 | AMS-5862J/BMS-7-240 | 0.063 | 1 | 5 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862JH/ BMS 7-240D | 0.125 | 3.625 | 12 |
| 15-5 Sheet 2D Finish Cond A | AMS-5862K / BMS 7-240D | 0.125 | 2.5 | 6 |

| Sheet H1025 | Spec | Thk | Width | Length |
|---------------------------------|-----------------------|------|-------|--------|
| 15-5 Rd. Bar Cond. H1025 | AMS-5862L / BMS 7-240 | 0.04 | 36 | 18.625 |
| 15-5 Rd. Bar Cond. H1025 | AMS-5862L / BMS 7-240 | 0.04 | 12 | 23.75 |

| Sheet | Spec | Thk | Width | Length |
|-------|------|-----|-------|--------|
|-------|------|-----|-------|--------|

15-5 Sheet 2D Finish Cond A **H925 38-45HRC 180/200KSI**

AMS-5862J/BMS-7-240

0.05

1

3

| Plate | Spec | Thk | Width | Length |
|-------|------|-----|-------|--------|
|-------|------|-----|-------|--------|

15-5 Plate H.R. **H900 /CG09**

AMS-5659M/AMS-5862 TY-2 UT. TEST

0.625

9.375

10.875

| Round Bar | Spec | Dia | Length |
|-----------|------|-----|--------|
|-----------|------|-----|--------|

15-5 Rd. Bar Cond-A Cold Finish

ASTM-A484-14 / AMS-5659-P

0.125

71.25

15-5 Rd. Bar Cond-A Cold Finish

ASTM-A484-14 / AMS-5659-P

0.4375

72

15-5 Rd. Bar Cond-A

ASTM-A484-14 / AMS-5659-P

0.5

47.5

15-5 Rd. Bar Cond-A

ASTM-A484-14 / AMS-5659-R

0.5

56.875

15-5 Rd. Bar Cond-A VAR

ASTM-A484/ AMS-5659

0.5625

55.75

15-5 Rd. Bar Cond-A **HT To 25-28 HRC**

ASTM-A484-16 / AMS-5659-R

0.5625

Andy B-4 Sel

48

15-5 Rd. Bar Cond-A

ASTM-A484/ AMS-5659

0.625

10

15-5 Rd. Bar Cond-A VAR

ASTM-A484-14A / AMS-5659R

0.75

130.25

15-5 Rd. Bar Cond-A **UT Type 1 Class A**

AMS-STD-2154 C / AMS-5659/I

0.75

134

15-5 Rd. Bar Cond-A

ASTM-A484-13A / AMS-5659R

0.875

11

15-5 Rd. Bar Cond-A VAR

ASTM-A484-14A/ AMS-5659S

0.875

154.5

15-5 Rd. Bar Cond-A VAR

ASTM-A484/ AMS-5659

1

12.25

15-5 Rd. Bar Cond-A VAR

ASTM-A484-14A/ AMS-5659S

1

57.875

15-5 Rd. Bar Cond-A VAR

ASTM-A484-14A/ AMS-5659S

1

48.5

| | | | |
|-----------------------------------|---|-------|---------|
| 15-5 Rd. Bar Cond-A VAR UT tested | ASTM-A484-14A/ AMS-5659R / BAC 5439J CL A | 1 | 72 |
| 15-5 Rd. Bar Cond-A VAR UT tested | ASTM-A484-14A/ AMS-5659R / BAC 5439J CL A | 1 | 144 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1.125 | 153.625 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1.125 | 153.5 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1.125 | 152 |
| 15-5 Rd. Bar Cond-A ESR HR | ASTM-A484/ AMS-5659N | 1.25 | 56.375 |
| 15-5 Rd. Bar Cond-A ESR HR Ty-2 | ASTM-A484/ AMS-5659N | 1.25 | 153.5 |
| 15-5 Rd. Bar Cond-A DMR-350 | ASTM-A484-13a / AMS-5659R | 1.5 | 120 |
| 15-5 Rd. Bar Cond-A | ASTM-A484-13a / AMS-5659P | 4.5 | 3.375 |
| 15-5 Rd. Bar Cond-A | ASTM-A484/ AMS-5659 | 7.5 | 1.059 |
| 15-5 Rd. Bar Cond-A | ASTM-A484/ AMS-5659 | 10 | 12 |

| Heat Treated Bar | Spec | Dia | Length |
|------------------|------|-----|--------|
|------------------|------|-----|--------|

| Heat Treated Bar | Spec | Dia | Length |
|------------------|------|-----|--------|
|------------------|------|-----|--------|

| | | | | |
|--|---------------------------|------|----|---------|
| 15-5 Rd. Bar Cond. H1025 | AMS-5862L / BMS 7-240 | 0.04 | 36 | 18.625 |
| 15-5 Rd. Bar Cond. H1025 | AMS-5862L / BMS 7-240 | 0.04 | 12 | 23.75 |
| 15-5 Rd. Bar Cond. H1025 | ASTM-A484-14A / AMS-5659P | 0.5 | | 109 |
| 15-5 Rd. Bar Cond. H1025 | ASTM-A484-16A / AMS-5659S | 0.75 | | 146.875 |
| 15-5 Rd. Bar Cond. H1025 | ASTM-A484-16A / AMS-5659S | 0.75 | | 108.5 |
| 15-5 Rd Bar Cond H1025 UT Insp. | AMS 5629, ASTM A 484-15 | 2 | | 4 |

| | | | |
|--|----------------------------|-------|--------|
| 15-5 Rd Bar Cond H1025 | AMS 5629S, ASTM A 484-15 | 2.125 | 36.5 |
| 15-5 Rect. Bar Ann. H1025 | UT TEST AMS-5659S | 2.625 | 8 |
| 15-5 Rd. Bar Var Ty-1 Cond. H1025 | ASTM-A484-13 / AMS-5659P | 2.875 | 35.875 |
| 15-5 Rd. Bar Var Ty-1 Cond. H1025 | ASTM-A-484-15 / AMS-5659R | 3.25 | 5.875 |
| 15-5 Rd. Bar Var Ty-1 Cond. H1025 | ASTM-A484-13 / AMS-5659P&R | 3.5 | 2.75 |
| 15-5 Rd. Bar Var Cond H1025 Hot Rolled Ann. Machine from 4.5" dia | ASTM-A484-16/ AMS-5659R | 4.25 | 2.75 |
| 15-5 Rd. Bar Var Cond H1025 | ASTM-A484-13/ AMS-5659R | 5.5 | 4.375 |
| 15-5 Rd. Bar Var Cond H1025 Type 1 | ASTM-A484-16/ AMS-5659R | 6.082 | 9.5 |
| 15-5 Rd. Bar Var Cond H1025 | ASTM-A484-13/ AMS-5659R | 7.5 | 8.375 |

| Rect Bar | Spec | Thk | Width | Length |
|--|----------------------------------|-----------|-------|--------|
| 15-5 Rect. Bar Cond-A Machined from 4.0" thk | ASTM-A484/ AMS-5659 | 0.25 | 7 | 12 |
| 15-5 Rect. Bar Cond-A Machined from 6.5" dia | UT TEST ASTM-A564-13 / AMS-5659R | .282-.410 | 6.25 | 20 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1 | 2 | 153.5 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1 | 2 | 140 |
| 15-5 Rd. Bar Cond-A VAR | ASTM-A484-14A/ AMS-5659S | 1 | 2 | 139.5 |
| 15-5 Rect. Bar Ann Hot Finish | AMS-5659R | 1.5 | 2 | 23 |
| 15-5 Rect. Bar Cond-A | UT TEST ASTM-A564-13 / AMS-5659P | 2 | 6.75 | 7 |

| | | | | | | | | |
|-----------------------|--------------|-----------------|------------------------------|--------------------------|-----------------|--------------------|-------|-------|
| 15-5 Rect. Bar Cond-A | | | ASTM-A564-13 / AMS-5659P | 2 | 7 | 21.5 | | |
| 15-5 Rect. Bar | H1025 | 34-42 HRC | cut from 5" X 16" rect bar | AMS-5659R | 2 | 3.5 | 5.375 | |
| 15-5 Rect. Bar Cond-A | | | ASTM-A484/ AMS-5659 | 2.25 | 3 | 3.25 | | |
| 15-5 Rect. Bar Cond-A | | | ASTM-A484/ AMS-5659 | 2.25 | 3 | 3 | | |
| 15-5 Rect. Bar Ann. | H1025 | 34-40 HRC | cut from 2.25" X 18" rect ba | UT TEST | AMS-5659R REV.A | 2.25 | 2.75 | 7.375 |
| 15-5 Rect. Bar Ann. | H1025 | 34-40 HRC | cut from 2.25" X 18" rect ba | UT TEST | AMS-5659R REV.A | 2.25 | 2.25 | 19.5 |
| 15-5 Rect. Bar | H1025 | 34-42 HRC | cut from 5" X 16" rect bar | AMS-5659R | 2.75 | 5 | 6 | |
| 15-5 Rect. Bar Cond-A | | Moon cut | from 6.5"dia | ASTM-A564-13 / AMS-5659P | 3" X 6.5" | See B/4 cut | 102 | |
| 15-5 Rect. Bar | H1025 | 34-42 HRC | cut from 5" X 16" rect bar | AMS-5659R | 0.75 | 1.75 | 6 | |
| 15-5 Rect. Bar | H1025 | AGE /CG09 | cut from 3" X 1.75" X | ASTM-A484/ AMS-5659 | 3 | 1.75 | 18 | |
| 15-5 Rect. Bar | H1025 | 34-42 HRC | cut from 5" X 16" rect bar | AMS-5659R | 5 | 5.75 | 7.5 | |
| 15-5 Rect. Bar | H1025 | 34-42 HRC | cut from 5" X 16" rect bar | AMS-5659R | 5 | 5.5 | 7 | |

| Square Bar | | | Spec | Thk | Width | Length |
|--------------------------|--|--|--------------------------|-------|-------|--------|
| 15-5 Sq. Bar Cond-A | | | AMS-5659 | 1.25 | 1.25 | 155.5 |
| 15-5 Sq. Bar Cond-A | | | AMS-5659 | 1.25 | 1.25 | 132.5 |
| 15-5 Sq. Bar Cond-A | | | AMS-5659 | 1.625 | 1.625 | 72 |
| 15-5 Sq. Bar Cond-A | | | AMS-5659 | 1.625 | 1.625 | 60.375 |
| 15-5 Sq. Bar Cond-A H.R. | | | AMS-5659R / ASTM A564-13 | 2 | 2 | 9.875 |

| Hex Bar | | | Spec | Thk | Width | Length |
|---------|--|--|------|-----|-------|--------|
|---------|--|--|------|-----|-------|--------|

15-5 Hex Bar Cond-A

ASTM-A484-13 / AMS-5659P

0.75

Hex

82

15-5 Hex Bar Cond-A

ASTM-A484-13 / AMS-5659P

0.75

Hex

51.75

