

# 600 All

Sheet	Spec.	Thk	Width	Length
Inco 600 Bright Annealed	AMS-5540M/ASTM-B168/01	0.012	19.625	25
Inco 600 CR Annealed Sheet	AMS-5540L/ASTM-B168-01	0.043	11	11.75
Inco 600 CR Annealed Sheet	AMS-5540K/ASTM-B168-06	0.063	5.5	41.875
Inco 600 CR Annealed Sheet	AMS-5540L/ASTM-B168/01	0.14	15.875	9.625
Inco 600 CR Annealed Sheet	AMS-5540L/ASTM-B168/01	0.14	7.75	20

Bar	Spec.	Dia	Length
Nickel 600 Rd. Bar Ground f. .1875"	AMS-5665M/ASTM-B166-06	0.0938	36
Nickel 600 CD , CG Rod	AMS-5665M/ASTM-B166-06	0.1875	35.5
Ni 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.1875	83.5
Ni 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.1875	72
Nickel 600 Rd. Bar Ann H.F.	AMS-5665M/ASTM-B166-11	0.25	72
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.5	72
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.5	39.25
Inconel 600 Rd. Bar. Ann. Hot Fin.	AMS-5665N / ASTM-B166-11	0.625	46.75
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	43.75

Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	49.5
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	49.875
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	161
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	130.875
Inconel 600 Rd.Bar Ann. Hot Finished	AMS-5665N / ASTM-B166-11	0.625	10

Tube	Spec.	OD	Wall	Length
Inconel 600 Tube Cold Finished bright Ann. Se:	AMS 5580L	0.125	0.02	35
Inconel 600 Tube Cold Finished bright Ann. Se:	AMS 5580L	0.125	0.02	48
Inconel 600 Tube Ann.	ASTM-B167-08	.25"od	.049"wall	79.75"
Inconel 600 Tube Ann.	ASTM-B167-06 Smls	0.875	0.049	145.75

Wire				
Nickel 600 Wire	ASTM B 666-11	.020"		1 # Coil
Inco 600 Wire C.D. Ann.	AMS-5687/N	0.0625		262